



## BEARING DRIVESHAFT, INC.



110 mm x 140 mm x 16 mm skf 61822 bearing

Bearing No. 61822

61822 Bearing 2D drawings and 3D CAD models

Size	140x110x16 mm
Bore Diameter	140 mm
Outer Diameter	110 mm
Width	16 mm
d	110 mm
D	140 mm
B	16 mm
d <sub>1</sub>	118.6 mm
D <sub>2</sub>	134.05 mm
r <sub>1,2</sub> - min.	1 mm
d <sub>a</sub> - min.	115 mm
D <sub>a</sub> - max.	135 mm
r <sub>a</sub> - max.	1 mm
Basic dynamic load rating - C	28.1 kN
Basic static load rating - C <sub>0</sub>	26 kN
Fatigue load limit - P <sub>u</sub>	1.2 kN
Reference speed	9500 r/min
Limiting speed	5600 r/min
Calculation factor - k <sub>r</sub>	0.015
Calculation factor - f <sub>0</sub>	13.6
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.514



## BEARING DRIVESHAFT, INC.

Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	110MM Bore; 140MM Outside Diameter; 16MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	61822 J
Weight / LBS	1.13
Bore	4.331 Inch   110 Millimeter
Outer Race Width	0.63 Inch   16 Millimeter
Outside Diameter	5.512 Inch   140 Millimeter
bore diameter:	110 mm
static load capacity:	26 kN
outside diameter:	140 mm
precision rating:	Not Rated
overall width:	16 mm



## BEARING DRIVESHAFT, INC.

finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	16 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	1 mm
snap ring included:	Without Snap Ring
maximum rpm:	5600 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	28.1 kN
$d_1$	118.6 mm
$D_2$	134.05 mm
$r_{1,2}$ min.	1 mm
$d_a$ min.	115 mm
$D_a$ max.	135 mm
$r_a$ max.	1 mm
Basic dynamic load rating C	28.1 kN
Basic static load rating $C_0$	26 kN
Fatigue load limit $P_u$	1.25 kN
Calculation factor $k_r$	0.015
Calculation factor $f_0$	13.6
Mass bearing	0.47 kg